

KN30S

Unità di aggraffatura da banco 3 ton



Il modello **KN30S** è una macchina aggraffatrice da banco con forza aggraffatura di 3 ton.

La macchina viene fornita di serie con regolazione centesimale, lampada per l'illuminazione della zona lavoro ed un braccio portabobina. La macchina dispone di un dispositivo per il bloccaggio rapido del miniapplicatore per ridurre al minimo i tempi di cambio lavorazione.

Su richiesta, la macchina può essere equipaggiata di sistema di controllo aggraffatura



Braccio porta bobina orientabile

KN30S

Forza aggraffatura	30 kN (3 ton)
Alimentazione elettrica	2P+PE 230V AC 50/60Hz
Potenza elettrica	1,8 kW (8A)
Livello sonoro	< 80Db dB(A)
Corsa standard	40 mm
Punto morto inferiore	min 132 - max 137 mm
Sezione filo	fino a 16 mm ² (AWG 5)
Cicli / h	5000
Peso	95 kg
Peso con imballo	110 kg
Dimensioni senza portabobina	mm 320 x 500 x 750 h
Dimensioni con imballo	mm 800 x 600 x 1040 h

Optional

Sistema di controllo aggraffatura - Base aggancio rapido - Kit pneumatico

Dati e misure sono indicativi e soggetti a variazioni senza preavviso. Alcuni tipi di cavi particolari potrebbero non essere lavorati nonostante rientrino nella gamma di sezioni indicate. KM Corporate sarà comunque lieta di eseguire prove e fornire campioni lavorati di filo.

KN30S

Bench unit 3 ton



Model **KN30S** is a bench crimping unit with crimping force of 3 tons.

The machine includes as standard feature centesimal adjustment, lamp for the working area lighting and reel holder bracket. The machine has a feature for quick clamping of the miniapplicator to minimize changeover times.

On request, the machine can be equipped with crimp force monitoring.



Revolving reel support bracket

KN30S

Crimping force	30 kN (3 ton)
Power supply	2P+PE 230V AC 50/60Hz
Power consumption	1,8 kW (8A)
Noise level	< 80Db dB(A)
Standard stroke, mm	40 mm
Lower dead center, mm	min 132 - max 137 mm
Wire cross-section	up to 16 mm ² (AWG 5)
Cycles/h	5000
Weight, kg	95 kg
Weight with packing	110 kg
Dimensions without coil holders	mm 320 x 500 x 750 h
Dimensions with packing	mm 800 x 600 x 1040 h

Optional

Crimping force monitor - Quick base kit - Pneumatic kit

All data and measures are indicative and can be changed without notice. Certain types of extremely hard, tough wires may not be able to be processed even if written within the indicated ranges. In case of doubt, KM Corporate is willing to produce samples of your wire.